CALLMASTER

ANNUNCIATOR PANEL

AUG 2018



16 CHANNEL ALARM PANEL

Callmaster Annunciator Panel for 4, 8, or 16 alarm indications. The light display is a modular light cabinet with individual widows sized $1\frac{3}{4}$ " x $3\frac{1}{2}$ ". Each window is illuminated by two lamps for increased reliability and uniform light distribution. Each alarm is configured and programmed into a Master Logic Controller (see Bulletin E2). On alarm the indicator light goes steady, and any remote lights or horns are activated. When the alarm is acknowledged the remote devices go off, and the panel indicator flashes until the alarm clears. A lamp test and alarm silencer switch is also provided.

16 Alarm Annunciator Panel, engraved light panel, programmed Master Logic Controller, output relays for remote alarm light and horn. Furnished with lightning protection and control breaker. Nema 12 enclosure 24" x 30" x 8". UL508A Listed Control Panel.

Complete Panel wired and tested.

Call for a custom quote for your specific requirements.

PHONE DIALER

ALARM MONITORING SYSTEM

AUG 2018



FEATURES

Monitors power, temperature, and other important conditions like pump failure, high or low tank level alarms. Automatically contacts you if unsafe or failure conditions occur. Allows you to contact your system from any telephone to receive status reports or listen to on-site sounds. The system communicates in simple voice-synthesized English. Battery backup is provided on all Master Level Control systems.

MODEL DL-400 DIALER

Provides 4 monitored conditions, temperature, and 3 user selectable inputs. Monitors sound and automatic AC power failure sensing. Dials up to 4 numbers, with up to 32 digits each. Continues dialing numbers in sequence, until acknowledged. Programmable intelligent dial out to beepers and pagers. Requires (6) 1.5 volt "C" cell batteries. Price installed and wired in a Master Level Control Panel.

MODEL DL-800 DIALER

Provides 8 monitored conditions, temperature, and 7 user selectable inputs. Monitors sound and automatic AC power failure sensing. Dials up to 8 numbers, with up to 32 digits each. Continues dialing numbers in sequence, until acknowledged. Programmable intelligent dial out to beepers and pagers. Requires (6) 1.5 volt "C" cell batteries. Price installed and wired in a Master Level Control Panel.